



# Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200

	<b>WHMIS Class E: Corrosive liquid. WHMIS CLASS D-2: Material causing other toxic effects. WHMIS Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).</b>	<b>Class: Irritating substance. Class: Corrosive material Class: Combustible liquid II having a flash point between 37.8°C (100°F) and 60.0°C (140°F).</b>
<b>WHMIS (Pictograms)</b>	<b>WHMIS (Classification)</b>	<b>HCS</b>

## Section 1. Chemical Product and Company Identification

<b>Product Name/ Trade name</b>	<b>Quat Stat SC</b>	<b>Code</b>	<b>340</b>
<b>Synonym</b>	Disinfectant/ Deodorant/ Virucide	<b>CAS #</b>	Mixture.
<b>Chemical Family</b>	Not available.	<b>Validation Date</b>	6/25/2009
<b>Chemical Formula</b>	Not applicable.	<b>Print Date</b>	6/25/2009
<b>Manufacturer/ Supplier</b>	Betco Corporation 1001 Brown Avenue Toledo, Oh 43607 (419) 241-2156	<b>In Case of Emergency</b>	Chemtrec (800) 424-9300
<b>TSCA</b>	<b>TSCA Inventory: All components listed or are exempt from listing.</b>		
<b>DSL/ NDSL</b>	<b>All components listed unless noted elsewhere on this MSDS</b>		

### Protective Clothing



## Section 2. Composition and Information on Ingredients

Name	CAS #	% by Weight	Exposure Limits	LC <sub>50</sub> /LD <sub>50</sub>
Quaternary Ammonium Chloride	68424-95-3	10 - 15	Not available.	Not available.
Quaternary Ammonium Chloride	68424-85-1	5 - 10	Not available.	Not available.
Nonionic Surfactant	127087-87-0	1 - 5	Not available.	Not available.
Ethyl Alcohol	64-17-5	0 - 5	TWA: 1000 ppm <b>OSHA (United States).</b> TWA: 1000 ppm	ORAL (LD50): Acute: 7060 mg/kg [Rat].

## Section 3. Hazards Identification

<b>Potential Acute Health Effects</b>	Very hazardous in case of skin contact (corrosive, irritant), of eye contact (irritant, corrosive). Hazardous in case of ingestion, of inhalation. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
<b>Potential Chronic Health Effects</b>	Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Over-exposure by inhalation may cause respiratory irritation.
<b>Carcinogenic Effects</b>	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

#### **Section 4. First Aid Measures**

<b>Eye Contact</b>	Hold eye open and rinse slowly and thoroughly with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor immediately for treatment advice.
<b>Skin Contact</b>	Rinse skin with plenty of water for 15 to 20 minutes. Call a poison control center or doctor for further treatment advice.
<b>Inhalation</b>	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible. Call a poison control center or doctor for further treatment advice.
<b>Ingestion</b>	Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person

#### **Section 5. Fire Fighting Measures**

<b>Products of Combustion</b>	These products are carbon oxides (CO, CO2).
<b>Fire Fighting Media and Instructions</b>	Use DRY chemicals, CO2, alcohol foam or water spray.
<b>Special Remarks on Fire Hazards</b>	Not available.
<b>Special Remarks on Explosion Hazards</b>	Not available.

#### **Section 6. Accidental Release Measures**

<b>Small Spill and Leak</b>	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.
<b>Large Spill and Leak</b>	Combustible liquid. Corrosive liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed.
<b>Personal Protection in Case of a Large Spill</b>	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

#### **Section 7. Handling and Storage**

<b>Precautions</b>	Keep container dry. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.
<b>Incompatibility</b>	Reactive with oxidizing agents.
<b>Storage</b>	Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of the reach of children. Not for use or storage in or around the home.

#### **Section 8. Exposure Controls/Personal Protection**

<b>Engineering Controls</b>	Good general ventilation should be sufficient to control airborne levels.
<b>Personal Protection</b>	
<i>Eyes</i>	Splash goggles.
<i>Body</i>	Lab coat.
<i>Respiratory</i>	Wear appropriate respirator when ventilation is inadequate.
<i>Hands</i>	Gloves (impervious).

**Protective Clothing  
(Pictograms)**



**Exposure Limits**

**Ethyl Alcohol**

TWA: 1000 (ppm)

TWA: 1000 (ppm) from OSHA (PEL) [United States]

Consult local authorities for acceptable exposure limits.

**Section 9. Physical and Chemical Properties**

<b>Physical State and Appearance</b>	Liquid.	<b>Odor</b>	Pleasant.
<b>Molecular Weight</b>	Not applicable.	<b>Taste</b>	
<b>pH</b>	13 [Basic.]	<b>Color</b>	Violet.
<b>Boiling/Condensation Point</b>	Not available.		
<b>Melting/Freezing Point</b>	Not available.		
<b>Critical Temperature</b>	Not available.		
<b>Instability Temperature</b>	Not available.		
<b>Specific Gravity</b>	1.01 (Water = 1)		
<b>Vapor Pressure</b>	Not Determined		
<b>Vapor Density</b>	Not Determined		
<b>Volatility</b>	Not available.		
<b>VOC</b>	Not available.		
<b>Evaporation Rate</b>	Not available.		
<b>Dispersion Properties</b>	See solubility in water.		
<b>Solubility</b>	Soluble in cold water, hot water.		
<b>The Product is:</b>	COMBUSTIBLE.		
<b>Auto-ignition Temperature</b>	Not available.		
<b>Flash Points</b>	CLOSED CUP: 51.667°C (125°F). (Tagliabue.)		
<b>Flammable Limits</b>	Not available.		
<b>Fire Hazards in Presence of Various Substances</b>	Not available.		
<b>Explosion Hazards in Presence of Various Substances</b>	Explosive in presence of open flames and sparks, of heat.		

### Section 10. Stability and Reactivity Data

Stability	The product is stable.
Incompatibility with Various Substances	Reactive with oxidizing agents.
Hazardous Decomposition Products	Not available.

### Section 11. Toxicological Information

Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 3030 mg/kg [Rat]. (Tetrasodium salt of ethylenediaminetetraacetic acid).
Acute Effects on Humans	<p><i>Eyes</i> Very hazardous in case of eye contact (irritant, corrosive). Inflammation of the eye is characterized by redness, watering, and itching. May cause corneal opacity.</p> <p><i>Skin</i> Sensitization of the product: Not available. Very hazardous in case of skin contact (corrosive, irritant). Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.</p> <p><i>Inhalation</i> Hazardous in case of inhalation. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Over-exposure by inhalation may cause respiratory irritation.</p> <p><i>Ingestion</i> May be fatal if swallowed. May cause burns to mouth, throat, and stomach. May cause headache, dizziness, nausea, and loss of concentration.</p>
Chronic Effects on Humans	Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Over-exposure by inhalation may cause respiratory irritation.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.

### Section 12. Ecological Information

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Products of Biodegradation	These products are carbon oxides (CO, CO2) and water.
Toxicity of the Products of Biodegradation	The products of degradation are less toxic than the product itself.
Special Remarks on the Products of Biodegradation	Not available.

### Section 13. Disposal Considerations

Waste Information	Dispose of in accordance with all applicable local, state and Federal regulations
Waste Stream	Not available.

## Section 14. Transport Information

DOT (U.S.A)  
(Pictograms)



TDG Classification Class 8: Corrosive material



PIN UN, Proper Shipping Name, PG Shipping name: CORROSIVE LIQUIDS, N.O.S. UNNA: 1760 PG: III

Maritime Transportation Not available.

Special Provisions for Transport Not available.

## Section 15. Other Regulatory Information and Pictograms

WHMIS (Classification) WHMIS Class E: Corrosive liquid. WHMIS CLASS D-2: Material causing other toxic effects. WHMIS Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).



Regulatory Lists CEPA DSL: No products were found.

Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications

**HCS (U.S.A.)** Class: Irritating substance.  
Class: Corrosive material  
Class: Combustible liquid II having a flash point between 37.8°C (100°F) and 60.0°C (140°F).

**USA Regulatory Lists** California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Ethylene Oxide < 1 ppm  
California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Ethylene Oxide < 1 ppm  
Massachusetts RTK: Ethylene Oxide


**DSD (EEC)** R10- Flammable.

**International Regulations Lists** No products were found.

Hazardous Material Information System (U.S.A.)

Health	3
Flammability	2
Physical Hazard	0

National Fire Protection Association (U.S.A.)



The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product. Specific Hazard

**Section 16. Other Information**

Validated by CRushton on 6/25/2009.

Verified by CRushton.

Printed 6/25/2009.

**Information Contact Betco Corporation**  
1001 Brown Avenue  
Toledo, Ohio 43607

Notice to Reader:

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

Validated on 6/25/2009.

**Quat Stat SC**

Page: 6/6

**Continued on Next Page**